



# Foundations of Informatics: a Bridging Course

**Part C: Context-Free Languages**

**Lesson 5: The Emptiness Problem for Context-Free Languages**

**Thomas Noll**

**Software Modeling and Verification Group**

**RWTH Aachen University**

<https://moves.rwth-aachen.de/people/noll/>

# The Emptiness Problem

---

## Emptiness Problem for CFL

Given CFG  $G = \langle N, \Sigma, P, S \rangle$ , decide whether  $L(G) = \emptyset$  or not.

# The Emptiness Problem

---

## Emptiness Problem for CFL

Given CFG  $G = \langle N, \Sigma, P, S \rangle$ , decide whether  $L(G) = \emptyset$  or not.

- Important problem with many applications
  - consistency of context-free language definitions
  - correctness properties of recursive programs
  - ...
- For regular languages this was easy: check in the corresponding DFA whether some final state is reachable from the initial state.
- Here: test whether start symbol is **productive**, i.e., whether it generates a terminal word

# The Emptiness Test

---

## Algorithm (Emptiness Test)

*Input:  $G = \langle N, \Sigma, P, S \rangle$*

*Question:  $L(G) = \emptyset$ ?*

*Procedure: mark every  $a \in \Sigma$  as productive;*

*repeat*

*if there is  $A \rightarrow \alpha \in P$  such that all symbols in  $\alpha$  productive then  
mark  $A$  as productive;*

*end;*

*until no further productive symbols found;*

*Output: “no” if  $S$  productive, otherwise “yes”*

# The Emptiness Test

## Algorithm (Emptiness Test)

*Input:*  $G = \langle N, \Sigma, P, S \rangle$

*Question:*  $L(G) = \emptyset$ ?

*Procedure:* mark every  $a \in \Sigma$  as productive;

repeat

if there is  $A \rightarrow \alpha \in P$  such that all symbols in  $\alpha$  productive then  
mark  $A$  as productive;

end;

until no further productive symbols found;

*Output:* “no” if  $S$  productive, otherwise “yes”

## Example

$$\begin{array}{l} G : S \rightarrow AB \mid CA \\ A \rightarrow a \\ B \rightarrow BC \mid AB \\ C \rightarrow aB \mid b \end{array}$$

# The Emptiness Test

## Algorithm (Emptiness Test)

*Input:*  $G = \langle N, \Sigma, P, S \rangle$

*Question:*  $L(G) = \emptyset?$

*Procedure:* **mark every  $a \in \Sigma$  as productive;**

    repeat

        if there is  $A \rightarrow \alpha \in P$  such that all symbols in  $\alpha$  productive then  
            mark  $A$  as productive;

    end;

    until no further productive symbols found;

*Output:* “no” if  $S$  productive, otherwise “yes”

## Example

$G : S \rightarrow AB \mid CA$

$A \rightarrow a$

$B \rightarrow BC \mid AB$

$C \rightarrow aB \mid b$

1. Initialisation

# The Emptiness Test

## Algorithm (Emptiness Test)

*Input:*  $G = \langle N, \Sigma, P, S \rangle$

*Question:*  $L(G) = \emptyset?$

*Procedure:* mark every  $a \in \Sigma$  as productive;

repeat

if there is  $A \rightarrow \alpha \in P$  such that all symbols in  $\alpha$  productive then  
mark  $A$  as productive;

end;

until no further productive symbols found;

*Output:* “no” if  $S$  productive, otherwise “yes”

## Example

$G : S \rightarrow AB \mid CA$

$A \rightarrow a$

$B \rightarrow BC \mid AB$

$C \rightarrow aB \mid b$

1. Initialisation

2. 1st iteration

# The Emptiness Test

## Algorithm (Emptiness Test)

*Input:*  $G = \langle N, \Sigma, P, S \rangle$

*Question:*  $L(G) = \emptyset?$

*Procedure:* mark every  $a \in \Sigma$  as productive;

repeat

if there is  $A \rightarrow \alpha \in P$  such that all symbols in  $\alpha$  productive then  
mark  $A$  as productive;

end;

until no further productive symbols found;

*Output:* “no” if  $S$  productive, otherwise “yes”

## Example

$G : S \rightarrow AB \mid CA$

$A \rightarrow a$

$B \rightarrow BC \mid AB$

$C \rightarrow aB \mid b$

1. Initialisation

2. 1st iteration

3. 2nd iteration



# The Emptiness Test

## Algorithm (Emptiness Test)

*Input:*  $G = \langle N, \Sigma, P, S \rangle$

*Question:*  $L(G) = \emptyset$ ?

*Procedure:* mark every  $a \in \Sigma$  as productive;

repeat

if there is  $A \rightarrow \alpha \in P$  such that all symbols in  $\alpha$  productive then  
mark  $A$  as productive;

end;

until no further productive symbols found;

*Output:* “no” if  $S$  productive, otherwise “yes”

## Example

$G : S \rightarrow AB \mid CA$

$A \rightarrow a$

$B \rightarrow BC \mid AB$

$C \rightarrow aB \mid b$

1. Initialisation

2. 1st iteration

3. 2nd iteration

$S$  productive  $\implies L(G) \neq \emptyset$

# Summary: The Emptiness Problem for Context-Free Languages

---

## Seen:

- Emptiness problem decidable based on productivity of symbols

# Summary: The Emptiness Problem for Context-Free Languages

---

## Seen:

- Emptiness problem decidable based on productivity of symbols

## Next:

- Closure properties of CFLs