



# Foundations of Informatics: a Bridging Course

**Part C: Context-Free Languages**

**Lesson 6: Closure Properties of Context-Free Languages**

**Thomas Noll**

**Software Modeling and Verification Group**

**RWTH Aachen University**

<https://moves.rwth-aachen.de/people/noll/>

## Positive Results

---

### Theorem

*The set of CFLs is closed under concatenation, union, and iteration.*

## Positive Results

---

### Theorem

*The set of CFLs is closed under concatenation, union, and iteration.*

### Proof.

For  $i = 1, 2$ , let  $G_i = \langle N_i, \Sigma, P_i, S_i \rangle$  with  $L_i := L(G_i)$  and  $N_1 \cap N_2 = \emptyset$ , and let  $S \notin N_1 \cup N_2$  be a fresh nonterminal. Then

## Positive Results

### Theorem

*The set of CFLs is closed under concatenation, union, and iteration.*

### Proof.

For  $i = 1, 2$ , let  $G_i = \langle N_i, \Sigma, P_i, S_i \rangle$  with  $L_i := L(G_i)$  and  $N_1 \cap N_2 = \emptyset$ , and let  $S \notin N_1 \cup N_2$  be a fresh nonterminal. Then

- $L_1 \cdot L_2$  is generated by  $G := \langle N, \Sigma, P, S \rangle$  with  $N := \{S\} \cup N_1 \cup N_2$  and

$$P := \{S \rightarrow S_1 S_2\} \cup P_1 \cup P_2$$

## Positive Results

### Theorem

*The set of CFLs is closed under concatenation, union, and iteration.*

### Proof.

For  $i = 1, 2$ , let  $G_i = \langle N_i, \Sigma, P_i, S_i \rangle$  with  $L_i := L(G_i)$  and  $N_1 \cap N_2 = \emptyset$ , and let  $S \notin N_1 \cup N_2$  be a fresh nonterminal. Then

- $L_1 \cdot L_2$  is generated by  $G := \langle N, \Sigma, P, S \rangle$  with  $N := \{S\} \cup N_1 \cup N_2$  and

$$P := \{S \rightarrow S_1 S_2\} \cup P_1 \cup P_2$$

- $L_1 \cup L_2$  is generated by  $G := \langle N, \Sigma, P, S \rangle$  with  $N := \{S\} \cup N_1 \cup N_2$  and

$$P := \{S \rightarrow S_1 \mid S_2\} \cup P_1 \cup P_2$$

## Positive Results

### Theorem

*The set of CFLs is closed under concatenation, union, and iteration.*

### Proof.

For  $i = 1, 2$ , let  $G_i = \langle N_i, \Sigma, P_i, S_i \rangle$  with  $L_i := L(G_i)$  and  $N_1 \cap N_2 = \emptyset$ , and let  $S \notin N_1 \cup N_2$  be a fresh nonterminal. Then

- $L_1 \cdot L_2$  is generated by  $G := \langle N, \Sigma, P, S \rangle$  with  $N := \{S\} \cup N_1 \cup N_2$  and

$$P := \{S \rightarrow S_1 S_2\} \cup P_1 \cup P_2$$

- $L_1 \cup L_2$  is generated by  $G := \langle N, \Sigma, P, S \rangle$  with  $N := \{S\} \cup N_1 \cup N_2$  and

$$P := \{S \rightarrow S_1 \mid S_2\} \cup P_1 \cup P_2$$

- $L_1^*$  is generated by  $G := \langle N, \Sigma, P, S \rangle$  with  $N := \{S\} \cup N_1$  and

$$P := \{S \rightarrow \varepsilon \mid S_1 S\} \cup P_1$$

□

# Negative Results

---

## Theorem

*The set of CFLs is not closed under intersection and complement.*

# Negative Results

## Theorem

*The set of CFLs is not closed under intersection and complement.*

## Proof.

- Intersection: both

$$L_1 := \{a^k b^l c^l \mid k, l \in \mathbb{N}\} \quad (\text{generated by } S \rightarrow AC, A \rightarrow aAb \mid \varepsilon, C \rightarrow Cc \mid \varepsilon)$$

and

$$L_2 := \{a^k b^l c^l \mid k, l \in \mathbb{N}\} \quad (\text{generated by } S \rightarrow AB, A \rightarrow aA \mid \varepsilon, B \rightarrow bBc \mid \varepsilon)$$

are CFLs,



# Negative Results

## Theorem

*The set of CFLs is not closed under intersection and complement.*

## Proof.

- Intersection: both

$$L_1 := \{a^k b^l c^l \mid k, l \in \mathbb{N}\} \quad (\text{generated by } S \rightarrow AC, A \rightarrow aAb \mid \varepsilon, C \rightarrow Cc \mid \varepsilon)$$

and

$$L_2 := \{a^k b^l c^l \mid k, l \in \mathbb{N}\} \quad (\text{generated by } S \rightarrow AB, A \rightarrow aA \mid \varepsilon, B \rightarrow bBc \mid \varepsilon)$$

are CFLs, but not

$$L_1 \cap L_2 = \{a^n b^n c^n \mid n \in \mathbb{N}\}$$

(without proof).

# Negative Results

## Theorem

*The set of CFLs is not closed under intersection and complement.*

## Proof.

- Intersection: both

$$L_1 := \{a^k b^l c^l \mid k, l \in \mathbb{N}\} \quad (\text{generated by } S \rightarrow AC, A \rightarrow aAb \mid \varepsilon, C \rightarrow Cc \mid \varepsilon)$$

and

$$L_2 := \{a^k b^l c^l \mid k, l \in \mathbb{N}\} \quad (\text{generated by } S \rightarrow AB, A \rightarrow aA \mid \varepsilon, B \rightarrow bBc \mid \varepsilon)$$

are CFLs, but not

$$L_1 \cap L_2 = \{a^n b^n c^n \mid n \in \mathbb{N}\}$$

(without proof).

- Complement: if CFLs were closed under complement, then also under intersection (as  $L_1 \cap L_2 = \overline{\overline{L_1} \cup \overline{L_2}}$ ).



# Overview of Decidability and Closure Results

---

Decidability Results			
Class	$w \in L$	$L = \emptyset$	$L_1 = L_2$
<b>Reg</b>	+	+	+
<b>CFL</b>	+	+	—

# Overview of Decidability and Closure Results

---

Decidability Results			
Class	$w \in L$	$L = \emptyset$	$L_1 = L_2$
<b>Reg</b>	+	+	+
<b>CFL</b>	+	+	—

Closure Results					
Class	$L_1 \cdot L_2$	$L_1 \cup L_2$	$L_1 \cap L_2$	$\bar{L}$	$L^*$
<b>Reg</b>	+	+	+	+	+
<b>CFL</b>	+	+	—	—	+

# Summary: Closure Properties of Context-Free Languages

---

## Seen:

- Closure under concatenation, union and iteration
- Non-closure under intersection and complement

# Summary: Closure Properties of Context-Free Languages

---

## Seen:

- Closure under concatenation, union and iteration
- Non-closure under intersection and complement

## Next:

- Automata model for CFLs