



Foundations of Informatics: a Bridging Course

Part C: Context-Free Languages

Lesson 8: Pushdown Automata and Context-Free Languages

Thomas Noll

Software Modeling and Verification Group

RWTH Aachen University

<https://moves.rwth-aachen.de/people/noll/>

PDA and Context-Free Languages I

Theorem

A language is context-free iff it is PDA-recognisable.

PDA and Context-Free Languages I

Theorem

A language is context-free iff it is PDA-recognisable.

Proof.

“ \Leftarrow ”: omitted

“ \Rightarrow ”: let $G = \langle N, \Sigma, P, S \rangle$ be a CFG. Construction of PDA \mathcal{A}_G recognising $L(G)$:

- \mathcal{A}_G simulates a derivation of G where always the leftmost nonterminal of a sentence is replaced (“leftmost derivation”)
- begin with S on pushdown
- if nonterminal on top: apply a corresponding production rule
- if terminal on top: match with next input symbol

(cf. formal construction on following slide)



PDA and Context-Free Languages II

Proof of Theorem C.1 (continued).

“ \Rightarrow ”: Formally, $\mathfrak{A}_G := \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is given by

- $Q := \{q_0\}$
- $\Gamma := N \cup \Sigma$
- $Z_0 := S$
- for each $A \rightarrow \alpha \in P$: $((q_0, A, \varepsilon), (q_0, \alpha)) \in \Delta$ (“expansion”)
- for each $a \in \Sigma$: $((q_0, a, a), (q_0, \varepsilon)) \in \Delta$ (“matching”)
- $F := Q$



PDA and Context-Free Languages II

Proof of Theorem C.1 (continued).

“ \Rightarrow ”: Formally, $\mathfrak{A}_G := \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is given by

- $Q := \{q_0\}$
- $\Gamma := N \cup \Sigma$
- $Z_0 := S$
- for each $A \rightarrow \alpha \in P$: $((q_0, A, \varepsilon), (q_0, \alpha)) \in \Delta$ (“expansion”)
- for each $a \in \Sigma$: $((q_0, a, a), (q_0, \varepsilon)) \in \Delta$ (“matching”)
- $F := Q$



Example (“Bracket language” given by $G : S \rightarrow \langle \rangle \mid \langle S \rangle \mid SS$)

$\mathfrak{A}_G = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ with

- $Q = F = \{q_0\}$
- $\Sigma = \{\langle, \rangle\}, \Gamma = \{S, \langle, \rangle\}$
- $Z_0 = S$
- Δ : $((q_0, S, \varepsilon), (q_0, \langle \rangle)) \quad ((q_0, \langle, \rangle), (q_0, \varepsilon))$
 $((q_0, S, \varepsilon), (q_0, \langle S \rangle)) \quad ((q_0, \rangle, \rangle), (q_0, \varepsilon))$
 $((q_0, S, \varepsilon), (q_0, SS))$

PDA and Context-Free Languages II

Proof of Theorem C.1 (continued).

“ \Rightarrow ”: Formally, $\mathfrak{A}_G := \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is given by

- $Q := \{q_0\}$
- $\Gamma := N \cup \Sigma$
- $Z_0 := S$
- for each $A \rightarrow \alpha \in P$: $((q_0, A, \varepsilon), (q_0, \alpha)) \in \Delta$ (“expansion”)
- for each $a \in \Sigma$: $((q_0, a, a), (q_0, \varepsilon)) \in \Delta$ (“matching”)
- $F := Q$



Example (“Bracket language” given by $G : S \rightarrow \langle \rangle \mid \langle S \rangle \mid SS$)

$\mathfrak{A}_G = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ with

- $Q = F = \{q_0\}$
- $\Sigma = \{\langle, \rangle\}, \Gamma = \{S, \langle, \rangle\}$
- $Z_0 = S$
- Δ : $((q_0, S, \varepsilon), (q_0, \langle \rangle))$ $((q_0, \langle, \rangle), (q_0, \varepsilon))$
 $((q_0, S, \varepsilon), (q_0, \langle S \rangle))$ $((q_0, \rangle, \rangle), (q_0, \varepsilon))$
 $((q_0, S, \varepsilon), (q_0, SS))$

Accepting run for input $w = \langle \rangle \langle \rangle \langle \rangle$:

$(q_0, S, \langle \rangle \langle \rangle \langle \rangle)$

PDA and Context-Free Languages II

Proof of Theorem C.1 (continued).

“ \Rightarrow ”: Formally, $\mathfrak{A}_G := \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is given by

- $Q := \{q_0\}$
- $\Gamma := N \cup \Sigma$
- $Z_0 := S$
- for each $A \rightarrow \alpha \in P$: $((q_0, A, \varepsilon), (q_0, \alpha)) \in \Delta$ (“expansion”)
- for each $a \in \Sigma$: $((q_0, a, a), (q_0, \varepsilon)) \in \Delta$ (“matching”)
- $F := Q$



Example (“Bracket language” given by $G : S \rightarrow \langle \rangle \mid \langle S \rangle \mid SS$)

$\mathfrak{A}_G = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ with

- $Q = F = \{q_0\}$
- $\Sigma = \{\langle, \rangle\}, \Gamma = \{S, \langle, \rangle\}$
- $Z_0 = S$
- Δ : $((q_0, S, \varepsilon), (q_0, \langle \rangle))$ $((q_0, \langle, \rangle), (q_0, \varepsilon))$
 $((q_0, S, \varepsilon), (q_0, \langle S \rangle))$ $((q_0, \rangle, \rangle), (q_0, \varepsilon))$
 $((q_0, S, \varepsilon), (q_0, SS))$

Accepting run for input $w = \langle \rangle \langle \rangle \langle \rangle$:

$$(q_0, S, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, SS, \langle \rangle \langle \rangle \langle \rangle)$$

PDA and Context-Free Languages II

Proof of Theorem C.1 (continued).

“ \Rightarrow ”: Formally, $\mathfrak{A}_G := \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is given by

- $Q := \{q_0\}$
- $\Gamma := N \cup \Sigma$
- $Z_0 := S$
- for each $A \rightarrow \alpha \in P$: $((q_0, A, \varepsilon), (q_0, \alpha)) \in \Delta$ (“expansion”)
- for each $a \in \Sigma$: $((q_0, a, a), (q_0, \varepsilon)) \in \Delta$ (“matching”)
- $F := Q$



Example (“Bracket language” given by $G : S \rightarrow \langle \rangle \mid \langle S \rangle \mid SS$)

$\mathfrak{A}_G = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ with

- $Q = F = \{q_0\}$
- $\Sigma = \{\langle, \rangle\}, \Gamma = \{S, \langle, \rangle\}$
- $Z_0 = S$
- Δ : $((q_0, S, \varepsilon), (q_0, \langle \rangle))$ $((q_0, \langle, \rangle), (q_0, \varepsilon))$
 $((q_0, \textcolor{red}{S}, \varepsilon), (q_0, \langle \textcolor{red}{S} \rangle))$ $((q_0, \rangle, \rangle), (q_0, \varepsilon))$
 $((q_0, S, \varepsilon), (q_0, SS))$

Accepting run for input $w = \langle \rangle \langle \rangle \langle \rangle$:

$$(q_0, S, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, \textcolor{red}{SS}, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, \langle \textcolor{red}{S} \rangle S, \langle \rangle \langle \rangle \langle \rangle)$$

PDA and Context-Free Languages II

Proof of Theorem C.1 (continued).

“ \Rightarrow ”: Formally, $\mathfrak{A}_G := \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is given by

- $Q := \{q_0\}$
- $\Gamma := N \cup \Sigma$
- $Z_0 := S$
- for each $A \rightarrow \alpha \in P$: $((q_0, A, \varepsilon), (q_0, \alpha)) \in \Delta$ (“expansion”)
- for each $a \in \Sigma$: $((q_0, a, a), (q_0, \varepsilon)) \in \Delta$ (“matching”)
- $F := Q$

□

Example (“Bracket language” given by $G : S \rightarrow \langle \rangle \mid \langle S \rangle \mid SS$)

$\mathfrak{A}_G = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ with

- $Q = F = \{q_0\}$
- $\Sigma = \{\langle, \rangle\}, \Gamma = \{S, \langle, \rangle\}$
- $Z_0 = S$
- Δ : $((q_0, S, \varepsilon), (q_0, \langle \rangle)) \quad ((q_0, \langle, \rangle), (q_0, \varepsilon))$
 $((q_0, S, \varepsilon), (q_0, \langle S \rangle)) \quad ((q_0, \rangle, \rangle), (q_0, \varepsilon))$
 $((q_0, S, \varepsilon), (q_0, SS))$

Accepting run for input $w = \langle \rangle \langle \rangle \langle \rangle$:

$$(q_0, S, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, SS, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, \langle S \rangle S, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, S \rangle S, \langle \rangle \langle \rangle \langle \rangle)$$

PDA and Context-Free Languages II

Proof of Theorem C.1 (continued).

“ \Rightarrow ”: Formally, $\mathfrak{A}_G := \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is given by

- $Q := \{q_0\}$
- $\Gamma := N \cup \Sigma$
- $Z_0 := S$
- for each $A \rightarrow \alpha \in P$: $((q_0, A, \varepsilon), (q_0, \alpha)) \in \Delta$ (“expansion”)
- for each $a \in \Sigma$: $((q_0, a, a), (q_0, \varepsilon)) \in \Delta$ (“matching”)
- $F := Q$

□

Example (“Bracket language” given by $G : S \rightarrow \langle \rangle \mid \langle S \rangle \mid SS$)

$\mathfrak{A}_G = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ with

- $Q = F = \{q_0\}$
- $\Sigma = \{\langle, \rangle\}, \Gamma = \{S, \langle, \rangle\}$
- $Z_0 = S$
- Δ : $((q_0, S, \varepsilon), (q_0, \langle \rangle)) \quad ((q_0, \langle, \rangle), (q_0, \varepsilon))$
 $((q_0, S, \varepsilon), (q_0, \langle S \rangle)) \quad ((q_0, \rangle, \rangle), (q_0, \varepsilon))$
 $((q_0, S, \varepsilon), (q_0, SS))$

Accepting run for input $w = \langle \rangle \langle \rangle \langle \rangle$:

$$\begin{aligned} & (q_0, S, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, SS, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, \langle S \rangle S, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, S, \langle \rangle \langle \rangle \langle \rangle) \\ & \vdash (q_0, \langle \rangle S, \langle \rangle \langle \rangle \langle \rangle) \end{aligned}$$

PDA and Context-Free Languages II

Proof of Theorem C.1 (continued).

“ \Rightarrow ”: Formally, $\mathfrak{A}_G := \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is given by

- $Q := \{q_0\}$
- $\Gamma := N \cup \Sigma$
- $Z_0 := S$
- for each $A \rightarrow \alpha \in P$: $((q_0, A, \varepsilon), (q_0, \alpha)) \in \Delta$ (“expansion”)
- for each $a \in \Sigma$: $((q_0, a, a), (q_0, \varepsilon)) \in \Delta$ (“matching”)
- $F := Q$

□

Example (“Bracket language” given by $G : S \rightarrow \langle \rangle \mid \langle S \rangle \mid SS$)

$\mathfrak{A}_G = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ with

- $Q = F = \{q_0\}$
- $\Sigma = \{\langle, \rangle\}, \Gamma = \{S, \langle, \rangle\}$
- $Z_0 = S$
- Δ : $((q_0, S, \varepsilon), (q_0, \langle \rangle))$ $((q_0, \langle, \rangle), (q_0, \varepsilon))$
 $((q_0, S, \varepsilon), (q_0, \langle S \rangle))$ $((q_0, \rangle, \rangle), (q_0, \varepsilon))$
 $((q_0, S, \varepsilon), (q_0, SS))$

Accepting run for input $w = \langle \rangle \langle \rangle \langle \rangle$:

$$\begin{aligned} & (q_0, S, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, SS, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, \langle S \rangle S, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, S \rangle S, \langle \rangle \langle \rangle \langle \rangle) \\ & \vdash (q_0, \langle \rangle \rangle S, \langle \rangle \rangle \langle \rangle) \vdash (q_0, \rangle \rangle S, \rangle \rangle \langle \rangle) \end{aligned}$$

PDA and Context-Free Languages II

Proof of Theorem C.1 (continued).

“ \Rightarrow ”: Formally, $\mathfrak{A}_G := \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is given by

- $Q := \{q_0\}$
- $\Gamma := N \cup \Sigma$
- $Z_0 := S$
- for each $A \rightarrow \alpha \in P$: $((q_0, A, \varepsilon), (q_0, \alpha)) \in \Delta$ (“expansion”)
- for each $a \in \Sigma$: $((q_0, a, a), (q_0, \varepsilon)) \in \Delta$ (“matching”)
- $F := Q$



Example (“Bracket language” given by $G : S \rightarrow \langle \rangle \mid \langle S \rangle \mid SS$)

$\mathfrak{A}_G = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ with

- $Q = F = \{q_0\}$
- $\Sigma = \{\langle, \rangle\}, \Gamma = \{S, \langle, \rangle\}$
- $Z_0 = S$
- Δ : $((q_0, S, \varepsilon), (q_0, \langle \rangle))$ $((q_0, \langle, \rangle), (q_0, \varepsilon))$
 $((q_0, S, \varepsilon), (q_0, \langle S \rangle))$ $((q_0, \rangle, \rangle), (q_0, \varepsilon))$
 $((q_0, S, \varepsilon), (q_0, SS))$

Accepting run for input $w = \langle \rangle \langle \rangle \langle \rangle$:

$$\begin{aligned} & (q_0, S, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, SS, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, \langle S \rangle S, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, S \rangle S, \langle \rangle \langle \rangle \langle \rangle) \\ & \vdash (q_0, \langle \rangle S, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, \rangle S, \rangle \langle \rangle \langle \rangle) \vdash (q_0, \rangle S, \rangle \langle \rangle) \end{aligned}$$

PDA and Context-Free Languages II

Proof of Theorem C.1 (continued).

“ \Rightarrow ”: Formally, $\mathfrak{A}_G := \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is given by

- $Q := \{q_0\}$
- $\Gamma := N \cup \Sigma$
- $Z_0 := S$
- for each $A \rightarrow \alpha \in P$: $((q_0, A, \varepsilon), (q_0, \alpha)) \in \Delta$ (“expansion”)
- for each $a \in \Sigma$: $((q_0, a, a), (q_0, \varepsilon)) \in \Delta$ (“matching”)
- $F := Q$

□

Example (“Bracket language” given by $G : S \rightarrow \langle \rangle \mid \langle S \rangle \mid SS$)

$\mathfrak{A}_G = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ with

- $Q = F = \{q_0\}$
- $\Sigma = \{\langle, \rangle\}, \Gamma = \{S, \langle, \rangle\}$
- $Z_0 = S$
- Δ : $((q_0, S, \varepsilon), (q_0, \langle \rangle)) \quad ((q_0, \langle, \langle \rangle), (q_0, \varepsilon))$
 $((q_0, S, \varepsilon), (q_0, \langle S \rangle)) \quad ((q_0, \rangle, \rangle), (q_0, \varepsilon))$
 $((q_0, S, \varepsilon), (q_0, SS))$

Accepting run for input $w = \langle \rangle \langle \rangle \langle \rangle$:

$$\begin{array}{l} (q_0, S, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, SS, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, \langle S \rangle S, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, S \rangle S, \langle \rangle \langle \rangle \langle \rangle) \\ \vdash (q_0, \langle \rangle \rangle S, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, \rangle \rangle S, \rangle \rangle \langle \rangle) \vdash (q_0, \rangle S, \rangle \langle \rangle) \vdash (q_0, S, \langle \rangle) \end{array}$$

PDA and Context-Free Languages II

Proof of Theorem C.1 (continued).

“ \Rightarrow ”: Formally, $\mathfrak{A}_G := \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is given by

- $Q := \{q_0\}$
- $\Gamma := N \cup \Sigma$
- $Z_0 := S$
- for each $A \rightarrow \alpha \in P$: $((q_0, A, \varepsilon), (q_0, \alpha)) \in \Delta$ (“expansion”)
- for each $a \in \Sigma$: $((q_0, a, a), (q_0, \varepsilon)) \in \Delta$ (“matching”)
- $F := Q$

□

Example (“Bracket language” given by $G : S \rightarrow \langle \rangle \mid \langle S \rangle \mid SS$)

$\mathfrak{A}_G = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ with

- $Q = F = \{q_0\}$
- $\Sigma = \{\langle, \rangle\}, \Gamma = \{S, \langle, \rangle\}$
- $Z_0 = S$
- Δ : $((q_0, S, \varepsilon), (q_0, \langle \rangle)) \quad ((q_0, \langle, \rangle), (q_0, \varepsilon))$
 $((q_0, S, \varepsilon), (q_0, \langle S \rangle)) \quad ((q_0, \rangle, \rangle), (q_0, \varepsilon))$
 $((q_0, S, \varepsilon), (q_0, SS))$

Accepting run for input $w = \langle \rangle \langle \rangle \langle \rangle$:

$$\begin{aligned}
 & (q_0, S, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, SS, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, \langle S \rangle S, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, S \rangle S, \langle \rangle \langle \rangle \langle \rangle) \\
 & \vdash (q_0, \langle \rangle \rangle S, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, \rangle \rangle S, \rangle \rangle \langle \rangle) \vdash (q_0, \rangle S, \rangle \langle \rangle) \vdash (q_0, S, \langle \rangle) \\
 & \vdash (q_0, \langle \rangle, \langle \rangle)
 \end{aligned}$$

PDA and Context-Free Languages II

Proof of Theorem C.1 (continued).

“ \Rightarrow ”: Formally, $\mathcal{A}_G := \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is given by

- $Q := \{q_0\}$
- $\Gamma := N \cup \Sigma$
- $Z_0 := S$
- for each $A \rightarrow \alpha \in P$: $((q_0, A, \varepsilon), (q_0, \alpha)) \in \Delta$ (“expansion”)
- for each $a \in \Sigma$: $((q_0, a, a), (q_0, \varepsilon)) \in \Delta$ (“matching”)
- $F := Q$

□

Example (“Bracket language” given by $G : S \rightarrow \langle \rangle \mid \langle S \rangle \mid SS$)

$\mathcal{A}_G = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ with

- $Q = F = \{q_0\}$
- $\Sigma = \{\langle, \rangle\}, \Gamma = \{S, \langle, \rangle\}$
- $Z_0 = S$
- Δ : $((q_0, S, \varepsilon), (q_0, \langle \rangle)) \quad ((q_0, \langle, \rangle), (q_0, \varepsilon))$
 $((q_0, S, \varepsilon), (q_0, \langle S \rangle)) \quad ((q_0, \rangle, \rangle), (q_0, \varepsilon))$
 $((q_0, S, \varepsilon), (q_0, SS))$

Accepting run for input $w = \langle \rangle \langle \rangle \langle \rangle$:

$$\begin{array}{l}
 (q_0, S, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, SS, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, \langle S \rangle S, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, S \rangle S, \langle \rangle \langle \rangle \langle \rangle) \\
 \vdash (q_0, \langle \rangle \rangle S, \langle \rangle \langle \rangle \langle \rangle) \vdash (q_0, \rangle \rangle S, \rangle \rangle \langle \rangle) \vdash (q_0, \rangle S, \rangle \langle \rangle) \vdash (q_0, S, \langle \rangle) \\
 \vdash (q_0, \langle, \rangle, \langle \rangle) \vdash (q_0, \rangle, \rangle)
 \end{array}$$

PDA and Context-Free Languages II

Proof of Theorem C.1 (continued).

“ \Rightarrow ”: Formally, $\mathfrak{A}_G := \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is given by

- $Q := \{q_0\}$
- $\Gamma := N \cup \Sigma$
- $Z_0 := S$
- for each $A \rightarrow \alpha \in P$: $((q_0, A, \varepsilon), (q_0, \alpha)) \in \Delta$ (“expansion”)
- for each $a \in \Sigma$: $((q_0, a, a), (q_0, \varepsilon)) \in \Delta$ (“matching”)
- $F := Q$

□

Example (“Bracket language” given by $G : S \rightarrow \langle \rangle \mid \langle S \rangle \mid SS$)

$\mathfrak{A}_G = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ with

- $Q = F = \{q_0\}$
- $\Sigma = \{\langle, \rangle\}, \Gamma = \{S, \langle, \rangle\}$
- $Z_0 = S$
- Δ : $((q_0, S, \varepsilon), (q_0, \langle \rangle)) \quad ((q_0, \langle, \rangle), (q_0, \varepsilon))$
 $((q_0, S, \varepsilon), (q_0, \langle S \rangle)) \quad ((q_0, \rangle, \rangle), (q_0, \varepsilon))$
 $((q_0, S, \varepsilon), (q_0, SS))$

Accepting run for input $w = \langle \rangle \langle \rangle \langle \rangle$:

$$\begin{array}{llll}
 (q_0, S, \langle \rangle \langle \rangle \langle \rangle) & \vdash & (q_0, SS, \langle \rangle \langle \rangle \langle \rangle) & \vdash & (q_0, \langle S \rangle S, \langle \rangle \langle \rangle \langle \rangle) & \vdash & (q_0, S \rangle S, \langle \rangle \langle \rangle \langle \rangle) \\
 \vdash & (q_0, \langle \rangle \rangle S, \langle \rangle \langle \rangle \langle \rangle) & \vdash & (q_0, \rangle \rangle S, \rangle \rangle \langle \rangle) & \vdash & (q_0, \rangle S, \rangle \langle \rangle) & \vdash & (q_0, S, \langle \rangle) \\
 \vdash & (q_0, \langle \rangle, \langle \rangle) & \vdash & (q_0, \rangle, \rangle) & \vdash & (q_0, \varepsilon, \varepsilon)
 \end{array}$$

Summary: Pushdown Automata and Context-Free Languages

Seen:

- Construction of PDA for given CFG (\Rightarrow parser generation!)
- Reverse direction also possible
- Thus: PDA and CFG equivalent

Summary: Pushdown Automata and Context-Free Languages

Seen:

- Construction of PDA for given CFG (\Rightarrow parser generation!)
- Reverse direction also possible
- Thus: PDA and CFG equivalent

Outlook:

- **Equivalence problem** for CFG and PDA (" $L(X_1) = L(X_2)$ "): generally undecidable, but decidable for DPDA
- **Pumping Lemma** for CFL (e.g., to prove that $\{a^n b^n c^n \mid n \geq 1\}$ not context-free)
- **Greibach Normal Form** for CFG
- Systematic construction of **deterministic and efficient** parsers for compilers (LL/LR grammars)
- Non-context-free grammars and languages (e.g., **context-sensitive** languages such as $\{a^n b^n c^n \mid n \geq 1\}$)