



Foundations of Informatics: a Bridging Course

Part C: Context-Free Languages

Lesson 7: Pushdown Automata

Thomas Noll

Software Modeling and Verification Group

RWTH Aachen University

<https://moves.rwth-aachen.de/people/noll/>

Pushdown Automata I

- **Goal:** introduce an automata model which **exactly accepts CFLs**
- **Clear:** DFA not sufficient
(missing “counting capability”, e.g. for $\{a^n b^n \mid n \geq 1\}$)

Pushdown Automata I

- **Goal:** introduce an automata model which **exactly accepts CFLs**
- **Clear:** DFA not sufficient
(missing “counting capability”, e.g. for $\{a^n b^n \mid n \geq 1\}$)
- DFA will be extended to **pushdown automata** by
 - adding a pushdown store which stores symbols from a pushdown alphabet and uses a special bottom symbol
 - adding push and pop operations to transitions

Pushdown Automata II

Definition

A **pushdown automaton (PDA)** is of the form $\mathfrak{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ where

- Q is a finite set of **states**
- Σ is the (finite) **input alphabet**
- Γ is the (finite) **pushdown alphabet**
- $\Delta \subseteq (Q \times \Gamma \times \Sigma_\epsilon) \times (Q \times \Gamma^*)$ is a finite set of **transitions**
- $q_0 \in Q$ is the **initial state**
- Z_0 is the **(pushdown) bottom symbol**
- $F \subseteq Q$ is a set of **final states**

Interpretation of $((q, Z, x), (q', \delta)) \in \Delta$: if the PDA \mathfrak{A} is in state q where Z is on top of the stack and x is the next input symbol (or empty), then \mathfrak{A} reads x , replaces Z by δ , and changes into the state q' .

Configurations, Runs, Acceptance

Definition

Let $\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ be a PDA.

- An element of $Q \times \Gamma^* \times \Sigma^*$ is called a **configuration** of \mathcal{A} .
- The **initial configuration** for input $w \in \Sigma^*$ is given by (q_0, Z_0, w) .
- The set of **final configurations** is given by $F \times \{\varepsilon\} \times \{\varepsilon\}$.
- If $((q, Z, x), (q', \delta)) \in \Delta$, then $(q, Z\gamma, xw) \vdash (q', \delta\gamma, w)$ for every $\gamma \in \Gamma^*$, $w \in \Sigma^*$.

Configurations, Runs, Acceptance

Definition

Let $\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ be a PDA.

- An element of $Q \times \Gamma^* \times \Sigma^*$ is called a **configuration** of \mathcal{A} .
- The **initial configuration** for input $w \in \Sigma^*$ is given by (q_0, Z_0, w) .
- The set of **final configurations** is given by $F \times \{\varepsilon\} \times \{\varepsilon\}$.
- If $((q, Z, x), (q', \delta)) \in \Delta$, then $(q, Z\gamma, xw) \vdash (q', \delta\gamma, w)$ for every $\gamma \in \Gamma^*$, $w \in \Sigma^*$.
- \mathcal{A} **accepts** $w \in \Sigma^*$ if $(q_0, Z_0, w) \vdash^* (q, \varepsilon, \varepsilon)$ for some $q \in F$.
- The **language accepted by** \mathcal{A} is $L(\mathcal{A}) := \{w \in \Sigma^* \mid \mathcal{A} \text{ accepts } w\}$.
- A language L is called **PDA-recognisable** if $L = L(\mathcal{A})$ for some PDA \mathcal{A} .
- Two PDA $\mathcal{A}_1, \mathcal{A}_2$ are called **equivalent** if $L(\mathcal{A}_1) = L(\mathcal{A}_2)$.

Examples of PDA I

Example (PDA for $L = \{a^n b^n \mid n \geq 1\}$)

$\mathfrak{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is given by

Examples of PDA I

Example (PDA for $L = \{a^n b^n \mid n \geq 1\}$)

$\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is given by

- $Q = \{q_0, q_1, q_2\}$
 - q_0 : construction of PD while reading a 's
 - q_1 : deconstruction while reading b 's
 - q_2 : accepting state

Examples of PDA I

Example (PDA for $L = \{a^n b^n \mid n \geq 1\}$)

$\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is given by

- $Q = \{q_0, q_1, q_2\}$
 - q_0 : construction of PD while reading a 's
 - q_1 : deconstruction while reading b 's
 - q_2 : accepting state
- $\Sigma = \{a, b\}$

Examples of PDA I

Example (PDA for $L = \{a^n b^n \mid n \geq 1\}$)

$\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is given by

- $Q = \{q_0, q_1, q_2\}$
 - q_0 : construction of PD while reading a 's
 - q_1 : deconstruction while reading b 's
 - q_2 : accepting state
- $\Sigma = \{a, b\}$
- $\Gamma = \{Z_0, Z\}$
 - Z_0 = bottom
 - $\#Z$ on PD = $\#a - \#b$ read so far
- $F = \{q_2\}$

Examples of PDA I

Example (PDA for $L = \{a^n b^n \mid n \geq 1\}$)

$\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is given by

- $Q = \{q_0, q_1, q_2\}$
 - q_0 : construction of PD while reading a 's
 - q_1 : deconstruction while reading b 's
 - q_2 : accepting state
- $\Sigma = \{a, b\}$
- $\Gamma = \{Z_0, Z\}$
 - Z_0 = bottom
 - $\#Z$ on PD = $\#a - \#b$ read so far
- $F = \{q_2\}$
- Δ :
 - $((q_0, Z_0, a), (q_0, ZZ_0))$ read first a
 - $((q_0, Z, a), (q_0, ZZ))$ read following a 's
 - $((q_0, Z, b), (q_1, \varepsilon))$ read first b
 - $((q_1, Z, b), (q_1, \varepsilon))$ read following b 's
 - $((q_1, Z_0, \varepsilon), (q_2, \varepsilon))$ change to final state

Examples of PDA I

Example (PDA for $L = \{a^n b^n \mid n \geq 1\}$)

$\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is given by

- $Q = \{q_0, q_1, q_2\}$
 - q_0 : construction of PD while reading a 's
 - q_1 : deconstruction while reading b 's
 - q_2 : accepting state
- $\Sigma = \{a, b\}$
- $\Gamma = \{Z_0, Z\}$
 - Z_0 = bottom
 - $\#Z$ on PD = $\#a - \#b$ read so far
- $F = \{q_2\}$
- Δ :
 - $((q_0, Z_0, a), (q_0, ZZ_0))$ read first a
 - $((q_0, Z, a), (q_0, ZZ))$ read following a 's
 - $((q_0, Z, b), (q_1, \varepsilon))$ read first b
 - $((q_1, Z, b), (q_1, \varepsilon))$ read following b 's
 - $((q_1, Z_0, \varepsilon), (q_2, \varepsilon))$ change to final state
- Observation: no transitions for
 - (q_0, Z_0, b) : input must start with a
 - (q_1, Z, a) : no a 's following b 's
 - (q_1, Z_0, b) : more b 's than a 's
 - ...

Examples of PDA I

Example (PDA for $L = \{a^n b^n \mid n \geq 1\}$)

$\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is given by

- $Q = \{q_0, q_1, q_2\}$
 - q_0 : construction of PD while reading a 's
 - q_1 : deconstruction while reading b 's
 - q_2 : accepting state
- $\Sigma = \{a, b\}$
- $\Gamma = \{Z_0, Z\}$
 - Z_0 = bottom
 - $\#Z$ on PD = $\#a - \#b$ read so far
- $F = \{q_2\}$
- Δ :
 - $((q_0, Z_0, a), (q_0, ZZ_0))$ read first a
 - $((q_0, Z, a), (q_0, ZZ))$ read following a 's
 - $((q_0, Z, b), (q_1, \varepsilon))$ read first b
 - $((q_1, Z, b), (q_1, \varepsilon))$ read following b 's
 - $((q_1, Z_0, \varepsilon), (q_2, \varepsilon))$ change to final state
- Observation: no transitions for
 - (q_0, Z_0, b) : input must start with a
 - (q_1, Z, a) : no a 's following b 's
 - (q_1, Z_0, b) : more b 's than a 's
 - ...

Accepting run of PDA for input $w = aabb$:

(remember: if $((q, Z, x), (q', \delta)) \in \Delta$, then $(q, Z\gamma, xw) \vdash (q', \delta\gamma, w)$)

$(q_0, Z_0, aabb)$

Examples of PDA I

Example (PDA for $L = \{a^n b^n \mid n \geq 1\}$)

$\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is given by

- $Q = \{q_0, q_1, q_2\}$
 - q_0 : construction of PD while reading a 's
 - q_1 : deconstruction while reading b 's
 - q_2 : accepting state
- $\Sigma = \{a, b\}$
- $\Gamma = \{Z_0, Z\}$
 - Z_0 = bottom
 - $\#Z$ on PD = $\#a - \#b$ read so far
- $F = \{q_2\}$
- Δ :
 - $((q_0, Z_0, a), (q_0, ZZ_0))$ read first a
 - $((q_0, Z, a), (q_0, ZZ))$ read following a 's
 - $((q_0, Z, b), (q_1, \varepsilon))$ read first b
 - $((q_1, Z, b), (q_1, \varepsilon))$ read following b 's
 - $((q_1, Z_0, \varepsilon), (q_2, \varepsilon))$ change to final state
- Observation: no transitions for
 - (q_0, Z_0, b) : input must start with a
 - (q_1, Z, a) : no a 's following b 's
 - (q_1, Z_0, b) : more b 's than a 's
 - ...

Accepting run of PDA for input $w = aabb$:

(remember: if $((q, Z, x), (q', \delta)) \in \Delta$, then $(q, Z\gamma, xw) \vdash (q', \delta\gamma, w)$)

$$(q_0, Z_0, aabb) \vdash (q_0, ZZ_0, abb)$$

Examples of PDA I

Example (PDA for $L = \{a^n b^n \mid n \geq 1\}$)

$\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is given by

- $Q = \{q_0, q_1, q_2\}$
 - q_0 : construction of PD while reading a 's
 - q_1 : deconstruction while reading b 's
 - q_2 : accepting state
- $\Sigma = \{a, b\}$
- $\Gamma = \{Z_0, Z\}$
 - Z_0 = bottom
 - $\#Z$ on PD = $\#a - \#b$ read so far
- $F = \{q_2\}$
- Δ :
 - $((q_0, Z_0, a), (q_0, ZZ_0))$ read first a
 - $((q_0, Z, a), (q_0, ZZ))$ read following a 's
 - $((q_0, Z, b), (q_1, \varepsilon))$ read first b
 - $((q_1, Z, b), (q_1, \varepsilon))$ read following b 's
 - $((q_1, Z_0, \varepsilon), (q_2, \varepsilon))$ change to final state
- Observation: no transitions for
 - (q_0, Z_0, b) : input must start with a
 - (q_1, Z, a) : no a 's following b 's
 - (q_1, Z_0, b) : more b 's than a 's
 - ...

Accepting run of PDA for input $w = aabb$:

(remember: if $((q, Z, x), (q', \delta)) \in \Delta$, then $(q, Z\gamma, xw) \vdash (q', \delta\gamma, w)$)

$$(q_0, Z_0, aabb) \vdash (q_0, ZZ_0, abb) \vdash (q_0, ZZZ_0, bb)$$

Examples of PDA I

Example (PDA for $L = \{a^n b^n \mid n \geq 1\}$)

$\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is given by

- $Q = \{q_0, q_1, q_2\}$
 - q_0 : construction of PD while reading a 's
 - q_1 : deconstruction while reading b 's
 - q_2 : accepting state
- $\Sigma = \{a, b\}$
- $\Gamma = \{Z_0, Z\}$
 - Z_0 = bottom
 - $\#Z$ on PD = $\#a - \#b$ read so far
- $F = \{q_2\}$
- Δ :
 - $((q_0, Z_0, a), (q_0, ZZ_0))$ read first a
 - $((q_0, Z, a), (q_0, ZZ))$ read following a 's
 - $((q_0, Z, b), (q_1, \varepsilon))$ read first b
 - $((q_1, Z, b), (q_1, \varepsilon))$ read following b 's
 - $((q_1, Z_0, \varepsilon), (q_2, \varepsilon))$ change to final state
- Observation: no transitions for
 - (q_0, Z_0, b) : input must start with a
 - (q_1, Z, a) : no a 's following b 's
 - (q_1, Z_0, b) : more b 's than a 's
 - ...

Accepting run of PDA for input $w = aabb$:

(remember: if $((q, Z, x), (q', \delta)) \in \Delta$, then $(q, Z\gamma, xw) \vdash (q', \delta\gamma, w)$)

$$(q_0, Z_0, aabb) \vdash (q_0, ZZ_0, abb) \vdash (q_0, ZZZ_0, bb) \vdash (q_1, ZZ_0, b)$$

Examples of PDA I

Example (PDA for $L = \{a^n b^n \mid n \geq 1\}$)

$\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is given by

- $Q = \{q_0, q_1, q_2\}$
 - q_0 : construction of PD while reading a 's
 - q_1 : deconstruction while reading b 's
 - q_2 : accepting state
- $\Sigma = \{a, b\}$
- $\Gamma = \{Z_0, Z\}$
 - Z_0 = bottom
 - $\#Z$ on PD = $\#a - \#b$ read so far
- $F = \{q_2\}$
- Δ :
 - $((q_0, Z_0, a), (q_0, ZZ_0))$ read first a
 - $((q_0, Z, a), (q_0, ZZ))$ read following a 's
 - $((q_0, Z, b), (q_1, \varepsilon))$ read first b
 - $((q_1, Z, b), (q_1, \varepsilon))$ read following b 's
 - $((q_1, Z_0, \varepsilon), (q_2, \varepsilon))$ change to final state
- Observation: no transitions for
 - (q_0, Z_0, b) : input must start with a
 - (q_1, Z, a) : no a 's following b 's
 - (q_1, Z_0, b) : more b 's than a 's
 - ...

Accepting run of PDA for input $w = aabb$:

(remember: if $((q, Z, x), (q', \delta)) \in \Delta$, then $(q, Z\gamma, xw) \vdash (q', \delta\gamma, w)$)

$$(q_0, Z_0, aabb) \vdash (q_0, ZZ_0, abb) \vdash (q_0, ZZZ_0, bb) \vdash (q_1, ZZ_0, b) \vdash (q_1, Z_0, \varepsilon)$$

Examples of PDA I

Example (PDA for $L = \{a^n b^n \mid n \geq 1\}$)

$\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is given by

- $Q = \{q_0, q_1, q_2\}$
 - q_0 : construction of PD while reading a 's
 - q_1 : deconstruction while reading b 's
 - q_2 : accepting state
- $\Sigma = \{a, b\}$
- $\Gamma = \{Z_0, Z\}$
 - Z_0 = bottom
 - $\#Z$ on PD = $\#a - \#b$ read so far
- $F = \{q_2\}$
- Δ :
 - $((q_0, Z_0, a), (q_0, ZZ_0))$ read first a
 - $((q_0, Z, a), (q_0, ZZ))$ read following a 's
 - $((q_0, Z, b), (q_1, \varepsilon))$ read first b
 - $((q_1, Z, b), (q_1, \varepsilon))$ read following b 's
 - $((q_1, Z_0, \varepsilon), (q_2, \varepsilon))$ change to final state
- Observation: no transitions for
 - (q_0, Z_0, b) : input must start with a
 - (q_1, Z, a) : no a 's following b 's
 - (q_1, Z_0, b) : more b 's than a 's
 - ...

Accepting run of PDA for input $w = aabb$:

(remember: if $((q, Z, x), (q', \delta)) \in \Delta$, then $(q, Z\gamma, xw) \vdash (q', \delta\gamma, w)$)

$(q_0, Z_0, aabb) \vdash (q_0, ZZ_0, abb) \vdash (q_0, ZZZ_0, bb) \vdash (q_1, ZZ_0, b) \vdash (q_1, Z_0, \varepsilon) \vdash (q_2, \varepsilon, \varepsilon)$

Examples of PDA II

Example (PDA for $L = \{ww^R \mid w \in \{a, b\}^*\}$ (palindromes of even length))

- Idea:
1. \mathcal{Q} pushes input w
 2. switches nondeterministically to the w^R recognition phase
 3. compares w and w^R symbol-wise by matching steps
 4. accepts with empty pushdown

Examples of PDA II

Example (PDA for $L = \{ww^R \mid w \in \{a, b\}^*\}$ (palindromes of even length))

- Idea:
1. \mathcal{A} pushes input w
 2. switches nondeterministically to the w^R recognition phase
 3. compares w and w^R symbol-wise by matching steps
 4. accepts with empty pushdown

Formally: $\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$

- $Q = \{q_0, q_1, q_2\}$

Examples of PDA II

Example (PDA for $L = \{ww^R \mid w \in \{a, b\}^*\}$ (palindromes of even length))

- Idea:
1. \mathcal{A} pushes input w
 2. switches nondeterministically to the w^R recognition phase
 3. compares w and w^R symbol-wise by matching steps
 4. accepts with empty pushdown

Formally: $\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$

- $Q = \{q_0, q_1, q_2\}$
- $\Sigma = \{a, b\}$

Examples of PDA II

Example (PDA for $L = \{ww^R \mid w \in \{a, b\}^*\}$ (palindromes of even length))

- Idea:
1. \mathcal{A} pushes input w
 2. switches nondeterministically to the w^R recognition phase
 3. compares w and w^R symbol-wise by matching steps
 4. accepts with empty pushdown

Formally: $\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$

- $Q = \{q_0, q_1, q_2\}$
- $\Sigma = \{a, b\}$
- $\Gamma = \{Z_0, a, b\}$
- $F = \{q_2\}$

Examples of PDA II

Example (PDA for $L = \{ww^R \mid w \in \{a, b\}^*\}$ (palindromes of even length))

- Idea:
1. \mathcal{A} pushes input w
 2. switches nondeterministically to the w^R recognition phase
 3. compares w and w^R symbol-wise by matching steps
 4. accepts with empty pushdown

Formally: $\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$

- $Q = \{q_0, q_1, q_2\}$
- $\Sigma = \{a, b\}$
- $\Gamma = \{Z_0, a, b\}$
- $F = \{q_2\}$

- $\Delta: ((q_0, Z, c), (q_0, cZ))$ for $Z \in \Gamma, c \in \Sigma$ (1)
- $((q_0, c, c), (q_1, \varepsilon))$ for $c \in \Sigma$ (2)
- $((q_0, Z_0, \varepsilon), (q_1, Z_0))$ (2)
- $((q_1, c, c), (q_1, \varepsilon))$ for $c \in \Sigma$ (3)
- $((q_1, Z_0, \varepsilon), (q_2, \varepsilon))$ (4)

Examples of PDA II

Example (PDA for $L = \{ww^R \mid w \in \{a, b\}^*\}$ (palindromes of even length))

- Idea:
1. \mathcal{A} pushes input w
 2. switches nondeterministically to the w^R recognition phase
 3. compares w and w^R symbol-wise by matching steps
 4. accepts with empty pushdown

Formally: $\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$

- $Q = \{q_0, q_1, q_2\}$
- $\Sigma = \{a, b\}$
- $\Gamma = \{Z_0, a, b\}$
- $F = \{q_2\}$

- $\Delta: ((q_0, Z, c), (q_0, cZ))$ for $Z \in \Gamma, c \in \Sigma$ (1)
- $((q_0, c, c), (q_1, \varepsilon))$ for $c \in \Sigma$ (2)
- $((q_0, Z_0, \varepsilon), (q_1, Z_0))$ (2)
- $((q_1, c, c), (q_1, \varepsilon))$ for $c \in \Sigma$ (3)
- $((q_1, Z_0, \varepsilon), (q_2, \varepsilon))$ (4)

Accepting run of PDA for input $w = abba$:

$(q_0, Z_0, abba)$

Examples of PDA II

Example (PDA for $L = \{ww^R \mid w \in \{a, b\}^*\}$ (palindromes of even length))

- Idea:
1. \mathcal{A} pushes input w
 2. switches nondeterministically to the w^R recognition phase
 3. compares w and w^R symbol-wise by matching steps
 4. accepts with empty pushdown

Formally: $\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$

- $Q = \{q_0, q_1, q_2\}$
- $\Sigma = \{a, b\}$
- $\Gamma = \{Z_0, a, b\}$
- $F = \{q_2\}$

- $\Delta: ((q_0, Z, c), (q_0, cZ))$ for $Z \in \Gamma, c \in \Sigma$ (1)
- $((q_0, c, c), (q_1, \varepsilon))$ for $c \in \Sigma$ (2)
- $((q_0, Z_0, \varepsilon), (q_1, Z_0))$ (2)
- $((q_1, c, c), (q_1, \varepsilon))$ for $c \in \Sigma$ (3)
- $((q_1, Z_0, \varepsilon), (q_2, \varepsilon))$ (4)

Accepting run of PDA for input $w = abba$:

$(q_0, Z_0, abba) \vdash (q_0, aZ_0, bba)$

Examples of PDA II

Example (PDA for $L = \{ww^R \mid w \in \{a, b\}^*\}$ (palindromes of even length))

- Idea:
1. \mathcal{A} pushes input w
 2. switches nondeterministically to the w^R recognition phase
 3. compares w and w^R symbol-wise by matching steps
 4. accepts with empty pushdown

Formally: $\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$

- $Q = \{q_0, q_1, q_2\}$
- $\Sigma = \{a, b\}$
- $\Gamma = \{Z_0, a, b\}$
- $F = \{q_2\}$

- $\Delta: ((q_0, Z, c), (q_0, cZ))$ for $Z \in \Gamma, c \in \Sigma$ (1)
- $((q_0, c, c), (q_1, \varepsilon))$ for $c \in \Sigma$ (2)
- $((q_0, Z_0, \varepsilon), (q_1, Z_0))$ (2)
- $((q_1, c, c), (q_1, \varepsilon))$ for $c \in \Sigma$ (3)
- $((q_1, Z_0, \varepsilon), (q_2, \varepsilon))$ (4)

Accepting run of PDA for input $w = abba$:

$(q_0, Z_0, abba) \vdash (q_0, aZ_0, bba) \vdash (q_0, baZ_0, ba)$

Examples of PDA II

Example (PDA for $L = \{ww^R \mid w \in \{a, b\}^*\}$ (palindromes of even length))

- Idea:
1. \mathcal{A} pushes input w
 2. switches nondeterministically to the w^R recognition phase
 3. compares w and w^R symbol-wise by matching steps
 4. accepts with empty pushdown

Formally: $\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$

- $Q = \{q_0, q_1, q_2\}$
- $\Sigma = \{a, b\}$
- $\Gamma = \{Z_0, a, b\}$
- $F = \{q_2\}$

- $\Delta: ((q_0, Z, c), (q_0, cZ))$ for $Z \in \Gamma, c \in \Sigma$ (1)
- $((q_0, c, c), (q_1, \varepsilon))$ for $c \in \Sigma$ (2)
- $((q_0, Z_0, \varepsilon), (q_1, Z_0))$ (2)
- $((q_1, c, c), (q_1, \varepsilon))$ for $c \in \Sigma$ (3)
- $((q_1, Z_0, \varepsilon), (q_2, \varepsilon))$ (4)

Accepting run of PDA for input $w = abba$:

$(q_0, Z_0, abba) \vdash (q_0, aZ_0, bba) \vdash (q_0, baZ_0, ba) \vdash (q_1, aZ_0, a)$

Examples of PDA II

Example (PDA for $L = \{ww^R \mid w \in \{a, b\}^*\}$ (palindromes of even length))

- Idea:
1. \mathcal{A} pushes input w
 2. switches nondeterministically to the w^R recognition phase
 3. compares w and w^R symbol-wise by matching steps
 4. accepts with empty pushdown

Formally: $\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$

- $Q = \{q_0, q_1, q_2\}$
- $\Sigma = \{a, b\}$
- $\Gamma = \{Z_0, a, b\}$
- $F = \{q_2\}$

- $\Delta: ((q_0, Z, c), (q_0, cZ))$ for $Z \in \Gamma, c \in \Sigma$ (1)
- $((q_0, c, c), (q_1, \varepsilon))$ for $c \in \Sigma$ (2)
- $((q_0, Z_0, \varepsilon), (q_1, Z_0))$ (2)
- $((q_1, c, c), (q_1, \varepsilon))$ for $c \in \Sigma$ (3)
- $((q_1, Z_0, \varepsilon), (q_2, \varepsilon))$ (4)

Accepting run of PDA for input $w = abba$:

$$(q_0, Z_0, abba) \vdash (q_0, aZ_0, bba) \vdash (q_0, baZ_0, ba) \vdash (q_1, aZ_0, a) \vdash (q_1, Z_0, \varepsilon)$$

Examples of PDA II

Example (PDA for $L = \{ww^R \mid w \in \{a, b\}^*\}$ (palindromes of even length))

- Idea:
1. \mathcal{A} pushes input w
 2. switches nondeterministically to the w^R recognition phase
 3. compares w and w^R symbol-wise by matching steps
 4. accepts with empty pushdown

Formally: $\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$

- $Q = \{q_0, q_1, q_2\}$
- $\Sigma = \{a, b\}$
- $\Gamma = \{Z_0, a, b\}$
- $F = \{q_2\}$

- $\Delta: ((q_0, Z, c), (q_0, cZ))$ for $Z \in \Gamma, c \in \Sigma$ (1)
- $((q_0, c, c), (q_1, \varepsilon))$ for $c \in \Sigma$ (2)
- $((q_0, Z_0, \varepsilon), (q_1, Z_0))$ (2)
- $((q_1, c, c), (q_1, \varepsilon))$ for $c \in \Sigma$ (3)
- $((q_1, Z_0, \varepsilon), (q_2, \varepsilon))$ (4)

Accepting run of PDA for input $w = abba$:

$$(q_0, Z_0, abba) \vdash (q_0, aZ_0, bba) \vdash (q_0, baZ_0, ba) \vdash (q_1, aZ_0, a) \vdash (q_1, Z_0, \varepsilon) \vdash (q_2, \varepsilon, \varepsilon)$$

Examples of PDA II

Example (PDA for $L = \{ww^R \mid w \in \{a, b\}^*\}$ (palindromes of even length))

- Idea:
1. \mathcal{A} pushes input w
 2. switches nondeterministically to the w^R recognition phase
 3. compares w and w^R symbol-wise by matching steps
 4. accepts with empty pushdown

Formally: $\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$

- $Q = \{q_0, q_1, q_2\}$
- $\Sigma = \{a, b\}$
- $\Gamma = \{Z_0, a, b\}$
- $F = \{q_2\}$

- $\Delta: ((q_0, Z, c), (q_0, cZ))$ for $Z \in \Gamma, c \in \Sigma$ (1)
- $((q_0, c, c), (q_1, \varepsilon))$ for $c \in \Sigma$ (2)
- $((q_0, Z_0, \varepsilon), (q_1, Z_0))$ (2)
- $((q_1, c, c), (q_1, \varepsilon))$ for $c \in \Sigma$ (3)
- $((q_1, Z_0, \varepsilon), (q_2, \varepsilon))$ (4)

Accepting run of PDA for input $w = abba$:

$(q_0, Z_0, abba) \vdash (q_0, aZ_0, bba) \vdash (q_0, baZ_0, ba) \vdash (q_1, aZ_0, a) \vdash (q_1, Z_0, \varepsilon) \vdash (q_2, \varepsilon, \varepsilon)$

Observation: \mathcal{A} is **nondeterministic** – in a configuration of the form (q_0, cv, cw) ($c \in \Sigma, v, w \in \Sigma^*$), both (1) and (2) are applicable.

Examples of PDA II

Example (PDA for $L = \{ww^R \mid w \in \{a, b\}^*\}$ (palindromes of even length))

- Idea:
1. \mathcal{A} pushes input w
 2. switches nondeterministically to the w^R recognition phase
 3. compares w and w^R symbol-wise by matching steps
 4. accepts with empty pushdown

Formally: $\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$

- $Q = \{q_0, q_1, q_2\}$
- $\Sigma = \{a, b\}$
- $\Gamma = \{Z_0, a, b\}$
- $F = \{q_2\}$

- $\Delta: ((q_0, Z, c), (q_0, cZ))$ for $Z \in \Gamma, c \in \Sigma$ (1)
- $((q_0, c, c), (q_1, \varepsilon))$ for $c \in \Sigma$ (2)
- $((q_0, Z_0, \varepsilon), (q_1, Z_0))$ (2)
- $((q_1, c, c), (q_1, \varepsilon))$ for $c \in \Sigma$ (3)
- $((q_1, Z_0, \varepsilon), (q_2, \varepsilon))$ (4)

Accepting run of PDA for input $w = abba$:

$$(q_0, Z_0, abba) \vdash (q_0, aZ_0, bba) \vdash (q_0, baZ_0, ba) \vdash (q_1, aZ_0, a) \vdash (q_1, Z_0, \varepsilon) \vdash (q_2, \varepsilon, \varepsilon)$$

Observation: \mathcal{A} is **nondeterministic** – in a configuration of the form (q_0, cv, cw) ($c \in \Sigma, v, w \in \Sigma^*$), both (1) and (2) are applicable. This yields **rejecting** runs, e.g.,

$$(q_0, Z_0, abba) \vdash (q_0, aZ_0, bba) \vdash (q_0, baZ_0, ba) \vdash (q_0, bbaZ_0, a) \vdash (q_0, abbaZ_0, \varepsilon) \nvdash$$

Deterministic PDA

Definition

A PDA $\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is called **deterministic (DPDA)** if for every $q \in Q, Z \in \Gamma$,

1. for every $x \in \Sigma_\epsilon$, there is at most one (q, Z, x) -transition in Δ and
2. if there is a (q, Z, a) -transition in Δ for some $a \in \Sigma$, then there is no (q, Z, ϵ) -transition in Δ .

Remark: this excludes two types of nondeterminism:

1. if $((q, Z, x), (q'_1, \delta_1)), ((q, Z, x), (q'_2, \delta_2)) \in \Delta$:
 $(q'_1, \delta_1 \gamma, w) \vdash (q, Z \gamma, xw) \vdash (q'_2, \delta_2 \gamma, w)$
2. if $((q, Z, a), (q'_1, \delta_1)), ((q, Z, \epsilon), (q'_2, \delta_2)) \in \Delta$:
 $(q'_1, \delta_1 \gamma, w) \vdash (q, Z \gamma, aw) \vdash (q'_2, \delta_2 \gamma, aw)$

Deterministic PDA

Definition

A PDA $\mathcal{A} = \langle Q, \Sigma, \Gamma, \Delta, q_0, Z_0, F \rangle$ is called **deterministic (DPDA)** if for every $q \in Q, Z \in \Gamma$,

1. for every $x \in \Sigma_\epsilon$, there is at most one (q, Z, x) -transition in Δ and
2. if there is a (q, Z, a) -transition in Δ for some $a \in \Sigma$, then there is no (q, Z, ϵ) -transition in Δ .

Remark: this excludes two types of nondeterminism:

1. if $((q, Z, x), (q'_1, \delta_1)), ((q, Z, x), (q'_2, \delta_2)) \in \Delta$:
 $(q'_1, \delta_1 \gamma, w) \vdash (q, Z \gamma, xw) \vdash (q'_2, \delta_2 \gamma, w)$
2. if $((q, Z, a), (q'_1, \delta_1)), ((q, Z, \epsilon), (q'_2, \delta_2)) \in \Delta$:
 $(q'_1, \delta_1 \gamma, w) \vdash (q, Z \gamma, aw) \vdash (q'_2, \delta_2 \gamma, aw)$

Corollary

In a DPDA, every configuration has at most one \vdash -successor.

Expressiveness of DPDA

One can show: determinism restricts the set of acceptable languages
(DPDA-recognisable languages are **closed under complement**, which is generally not true for PDA-recognisable languages)

Expressiveness of DPDA

One can show: determinism restricts the set of acceptable languages (DPDA-recognisable languages are **closed under complement**, which is generally not true for PDA-recognisable languages)

Example

The set of palindromes of even length is PDA-recognisable, but not DPDA-recognisable (without proof).

Summary: Pushdown Automata

Seen:

- Extension of finite automata by pushdown store
- Enables “counting” (e.g., $\{a^n b^n \mid n \geq 1\}$)
- Determinism restricts expressivity (in contrast to finite automata)

Summary: Pushdown Automata

Seen:

- Extension of finite automata by pushdown store
- Enables “counting” (e.g., $\{a^n b^n \mid n \geq 1\}$)
- Determinism restricts expressivity (in contrast to finite automata)

Next:

- Relation between PDA and context-free languages