



Foundations of Informatics: a Bridging Course

Part C: Context-Free Languages

Lesson 2: Context-Free vs. Regular Languages

Thomas Noll

Software Modeling and Verification Group

RWTH Aachen University

<https://moves.rwth-aachen.de/people/noll/>

Context-Free vs. Regular Languages

Theorem

1. *Every regular language is context-free.*
2. *There exist CFLs which are not regular.*

(Thus: regular languages are a **proper subset** of CFLs.)

Context-Free vs. Regular Languages

Theorem

1. *Every regular language is context-free.*
2. *There exist CFLs which are not regular.*

(Thus: regular languages are a **proper subset** of CFLs.)

Proof.

1. Let L be a regular language, and let $\mathcal{A} = \langle Q, \Sigma, \delta, q_0, F \rangle$ be a DFA which recognises L .
 $G_{\mathcal{A}} := \langle N, \Sigma, P, S \rangle$ is defined as follows:
 - $N := Q, S := q_0$
 - if $\delta(q, a) = q'$, then $q \rightarrow aq' \in P$
 - if $q \in F$, then $q \rightarrow \varepsilon \in P$

Obviously a w -labelled run in \mathcal{A} from q_0 to F corresponds to a derivation of w in $G_{\mathcal{A}}$, and vice versa. Thus $L(\mathcal{A}) = L(G_{\mathcal{A}})$ (example on the following slide).


2. An example is $\{a^n b^n \mid n \in \mathbb{N}\}$ (see Lesson 1).

Intuitive reason for non-regularity: recognising this language requires “unbounded counting” capability. □

From Regular to Context-Free Languages

Example


DFA $\mathfrak{A} = \langle Q, \Sigma, \delta, q_0, F \rangle$:



From Regular to Context-Free Languages

Example

DFA $\mathcal{A} = \langle Q, \Sigma, \delta, q_0, F \rangle$:




Corresponding CFG $G_{\mathcal{A}} := \langle N, \Sigma, P, S \rangle$
with $N := Q$, $S := q_0$:

From Regular to Context-Free Languages

Example

DFA $\mathcal{A} = \langle Q, \Sigma, \delta, q_0, F \rangle$:




Corresponding CFG $G_{\mathcal{A}} := \langle N, \Sigma, P, S \rangle$
with $N := Q$, $S := q_0$:

$q_0 \rightarrow a q_1 \mid b q_2$

From Regular to Context-Free Languages

Example

DFA $\mathcal{A} = \langle Q, \Sigma, \delta, q_0, F \rangle$:




Corresponding CFG $G_{\mathcal{A}} := \langle N, \Sigma, P, S \rangle$
with $N := Q$, $S := q_0$:

$$\begin{array}{l} q_0 \rightarrow a q_1 \mid b q_2 \\ q_1 \rightarrow a q_2 \mid b q_1 \mid \varepsilon \end{array}$$

From Regular to Context-Free Languages

Example

DFA $\mathcal{A} = \langle Q, \Sigma, \delta, q_0, F \rangle$:




Corresponding CFG $G_{\mathcal{A}} := \langle N, \Sigma, P, S \rangle$
with $N := Q$, $S := q_0$:

$$\begin{array}{l} q_0 \rightarrow a q_1 \mid b q_2 \\ q_1 \rightarrow a q_2 \mid b q_1 \mid \varepsilon \\ q_2 \rightarrow a q_3 \mid b q_3 \end{array}$$

From Regular to Context-Free Languages

Example

DFA $\mathcal{A} = \langle Q, \Sigma, \delta, q_0, F \rangle$:




Corresponding CFG $G_{\mathcal{A}} := \langle N, \Sigma, P, S \rangle$
with $N := Q$, $S := q_0$:

q_0	\rightarrow	$a q_1$	$ $	$b q_2$
q_1	\rightarrow	$a q_2$	$ $	$b q_1$
q_2	\rightarrow	$a q_3$	$ $	$b q_3$
q_3	\rightarrow	$a q_1$	$ $	$b q_1$

From Regular to Context-Free Languages

Example

DFA $\mathcal{A} = \langle Q, \Sigma, \delta, q_0, F \rangle$:



Corresponding CFG $G_{\mathcal{A}} := \langle N, \Sigma, P, S \rangle$
with $N := Q$, $S := q_0$:

$$\begin{array}{l} q_0 \rightarrow a q_1 \mid b q_2 \\ q_1 \rightarrow a q_2 \mid b q_1 \mid \varepsilon \\ q_2 \rightarrow a q_3 \mid b q_3 \\ q_3 \rightarrow a q_1 \mid b q_1 \end{array}$$


E.g., \mathcal{A} 's run on input $baab \in L(\mathcal{A})$ is simulated by the following derivation in $G_{\mathcal{A}}$:

q_0

From Regular to Context-Free Languages

Example

DFA $\mathcal{A} = \langle Q, \Sigma, \delta, q_0, F \rangle$:



Corresponding CFG $G_{\mathcal{A}} := \langle N, \Sigma, P, S \rangle$
with $N := Q$, $S := q_0$:

$$\begin{array}{l} q_0 \rightarrow a q_1 \mid b q_2 \\ q_1 \rightarrow a q_2 \mid b q_1 \mid \varepsilon \\ q_2 \rightarrow a q_3 \mid b q_3 \\ q_3 \rightarrow a q_1 \mid b q_1 \end{array}$$


E.g., \mathcal{A} 's run on input $baab \in L(\mathcal{A})$ is simulated by the following derivation in $G_{\mathcal{A}}$:

$$q_0 \Rightarrow b q_2$$

From Regular to Context-Free Languages

Example

DFA $\mathcal{A} = \langle Q, \Sigma, \delta, q_0, F \rangle$:



Corresponding CFG $G_{\mathcal{A}} := \langle N, \Sigma, P, S \rangle$
with $N := Q$, $S := q_0$:

$q_0 \rightarrow$	$a q_1$	$ $	$b q_2$
$q_1 \rightarrow$	$a q_2$	$ $	$b q_1$
$q_2 \rightarrow$	$a q_3$	$ $	$b q_3$
$q_3 \rightarrow$	$a q_1$	$ $	$b q_1$


E.g., \mathcal{A} 's run on input $baab \in L(\mathcal{A})$ is simulated by the following derivation in $G_{\mathcal{A}}$:

$$q_0 \Rightarrow b q_2 \Rightarrow b a q_3$$

From Regular to Context-Free Languages

Example

DFA $\mathcal{A} = \langle Q, \Sigma, \delta, q_0, F \rangle$:



Corresponding CFG $G_{\mathcal{A}} := \langle N, \Sigma, P, S \rangle$
with $N := Q$, $S := q_0$:

$q_0 \rightarrow$	$a q_1$	$ $	$b q_2$
$q_1 \rightarrow$	$a q_2$	$ $	$b q_1$
$q_2 \rightarrow$	$a q_3$	$ $	$b q_3$
$q_3 \rightarrow$	$a q_1$	$ $	$b q_1$


E.g., \mathcal{A} 's run on input $baab \in L(\mathcal{A})$ is simulated by the following derivation in $G_{\mathcal{A}}$:

$$q_0 \Rightarrow b q_2 \Rightarrow b a q_3 \Rightarrow b a a q_1$$

From Regular to Context-Free Languages

Example

DFA $\mathcal{A} = \langle Q, \Sigma, \delta, q_0, F \rangle$:



Corresponding CFG $G_{\mathcal{A}} := \langle N, \Sigma, P, S \rangle$
with $N := Q$, $S := q_0$:

$q_0 \rightarrow$	$a q_1$	$ $	$b q_2$
$q_1 \rightarrow$	$a q_2$	$ $	$b q_1$
$q_2 \rightarrow$	$a q_3$	$ $	$b q_3$
$q_3 \rightarrow$	$a q_1$	$ $	$b q_1$


E.g., \mathcal{A} 's run on input $baab \in L(\mathcal{A})$ is simulated by the following derivation in $G_{\mathcal{A}}$:

$$q_0 \Rightarrow b q_2 \Rightarrow b a q_3 \Rightarrow b a a q_1 \Rightarrow b a a b q_1$$

From Regular to Context-Free Languages

Example

DFA $\mathcal{A} = \langle Q, \Sigma, \delta, q_0, F \rangle$:



Corresponding CFG $G_{\mathcal{A}} := \langle N, \Sigma, P, S \rangle$
with $N := Q$, $S := q_0$:

$q_0 \rightarrow$	$a q_1$	$ $	$b q_2$
$q_1 \rightarrow$	$a q_2$	$ $	$b q_1$
$q_2 \rightarrow$	$a q_3$	$ $	$b q_3$
$q_3 \rightarrow$	$a q_1$	$ $	$b q_1$

E.g., \mathcal{A} 's run on input $baab \in L(\mathcal{A})$ is simulated by the following derivation in $G_{\mathcal{A}}$:

$$q_0 \Rightarrow b q_2 \Rightarrow b a q_3 \Rightarrow b a a q_1 \Rightarrow b a a b q_1 \Rightarrow b a a b$$

Summary: Context-Free vs. Regular Languages

Seen:

- CFLs are more expressive than regular languages

Summary: Context-Free vs. Regular Languages

Seen:

- CFLs are more expressive than regular languages

Next:

- Decidability of word problem